

100 Clemson Research Blvd., Anderson, SC 29625
Phone 864.646.8453 Fax 864.646.2821
Email testing@tcnatile.com Web www.TCNAtile.com

August 26, 2019

Solitrade/SoliBlock Floor HP Attn: Mark Haddad 1235 East Blvd. 207 Charlotte, NC 28203

Dear Mr. Haddad,

Tile Council of North America has tested the samples you submitted. Test report TCNA-0756-19 is enclosed. Note, the results within this report were first reported in TCNA test report TCNA-0278-15. If you have any questions or concerns, please contact us.

Best Regards,

TILE COUNCIL OF NORTH AMERICA, INC.

Katelyn Simpson Laboratory Manager

Enclosures



100 Clemson Research Blvd., Anderson, SC 29625
Phone 864.646.8453 Fax 864.646.2821
Email testing@tcnatile.com Web www.TCNAtile.com

TCNA TEST REPORT NUMBER: TCNA-0756-19 PAGE: 1 OF 7

TEST REQUESTED BY: Solitrade/SoliBlock Floor HP

TEST SUBJECT MATERIAL: Identified by client as: "SoliBlock Floor HP+"

**TEST DATE:** August 22-24, 2015

**TEST PROCEDURE:** ASTM C627: "A Standard Test Method for Evaluating Ceramic Floor Tile

**Installation Systems Using the Robinson-Type Floor Tester**"

### **TEST AND MATERIAL DESCRIPTION:**

As per client's request, the following materials were used for the preparation of the testing pad.

Material Description			
Item	Product name and size	<b>Product Codes</b>	Provided By:
#			
1	Concrete base with a smooth finish	N/A	TCNA
	Nominal Size: 48" x 48" x 2" (1219 mm x 1219 mm x 51 mm)		
2	Laticrete 253 Gold thin-set	0253-0050-22	Client
3	SoliBlock Floor HP+	Not Provided	Client
4	12" x 12" Crossville porcelain tiles	A825	TCNA
5	Laticrete Permacolor Select grout	2678-1001-2	Client

#### TYPE OF INSTALLATION:

# All the materials used were specified by the client and the tested assembly was built per the client's instructions.

The system consisted of a concrete subfloor with underlayment, and with porcelain tile. Further details about the installation are provided below.

### Base and Underlayment:

The installation of the underlayment was performed by a TCNA representative. The installation procedures are outlined below.

A 48" x 48" x 2" concrete base was prepared and cured for more than 28 days prior to use.

Laticrete 253 Gold thin-set mortar, mixed per manufacturer's instructions (mix ratio 22.9:100 by weight), was troweled over the concrete with a 3/32" V-notched trowel. The thin-set first keyed in with the flat side of the trowel then combed with the notched side to form parallel ridges. The SoliBlock Floor HP+ sound control membrane was cut to 48" x 48" and laid in the thin-set. Once in place the mat was rolled with a 35 pound roller.



100 Clemson Research Blvd., Anderson, SC 29625
Phone 864.646.8453 Fax 864.646.2821
Email testing@tcnatile.com Web www.TCNAtile.com

TCNA TEST REPORT NUMBER: TCNA-0756-19 PAGE: 2 OF 7

# Tile preparation:

The tiles were nominal size 12" x 12" and were installed in full pieces in the wheel path of the Robinson floor tester.

### Tile and Grout:

All tile installation and grouting was performed by a TCNA representative. The installation procedures are outlined below

Laticrete 253 thin-set mortar, mixed per manufacturer's instructions (mix ratio 22.9:100 by weight), was troweled over the underlayment with a 1/4"x 3/8" square-notched trowel. The thin-set first keyed in with the flat side of the trowel then combed with the notched side to form parallel ridges. The 12" x 12" Crossville porcelain tiles were back buttered with a skim coat before setting. Once set, the tiles were allowed to cure for 24 hours before grouting.

Laticrete Permacolor Select grout, mixed per manufacturer's instructions (mix ratio 16.7:100), was forced into the 1/16" grout joints with a rubber float. Excess grout was removed with the edge of the float. The grout was allowed to set up for approximately 20 minutes before the installation was cleaned with a sponge and water. The grouted installation was subsequently allowed to cure for 15 days per the client's request.

### **TEST RESULTS:**

The installation completed six cycles with no evidence of damage to the tiles or grout joints. At the completion of cycle seven (hard rubber wheels, three hundred pounds per wheel), there were four broken tiles and one spalled grout joints. All evaluation criteria were based on 8 tiles and 8 grout joints in the wheel path of the Robinson-Type Floor Tester.

# **HANDBOOK CLASSIFICATIONS\*:**

Classification	Cycles
Residential	Passes cycles 1-3
Light	Passes cycles 1-6
Moderate	Passes cycles 1-10
Heavy	Passes cycles 1-12
Extra Heavy	Passes cycles 1-14

<sup>\*</sup>For more detailed information, refer to the TCNA Handbook for Ceramic, Glass, and Stone Tile Installation.



100 Clemson Research Blvd., Anderson, SC 29625
Phone 864.646.8453 Fax 864.646.2821
Email testing@tcnatile.com Web www.TCNAtile.com

TCNA TEST REPORT NUMBER: TCNA-0756-19 PAGE: 3 OF 7

**Appendix:** Photos




Image 1: Full assembly after testing



100 Clemson Research Blvd., Anderson, SC 29625
Phone 864.646.8453 Fax 864.646.2821
Email testing@tcnatile.com Web www.TCNAtile.com

TCNA TEST REPORT NUMBER: TCNA-0756-19 PAGE: 4 OF 7



Image 2: Broken tile



100 Clemson Research Blvd., Anderson, SC 29625 Phone 864.646.8453 Fax 864.646.2821 Email testing@tcnatile.com Web www.TCNAtile.com

TCNA TEST REPORT NUMBER: TCNA-0756-19




Image 3: Broken tile



100 Clemson Research Blvd., Anderson, SC 29625 Phone 864.646.8453 Fax 864.646.2821 Email testing@tcnatile.com Web www.TCNAtile.com

TCNA TEST REPORT NUMBER: TCNA-0756-19



**Image 4**: Broken tile and spalled grout joint

# DISCLAIMER AND LIMITATION OF LIABILITY

This report is provided for the sole use of the client and no one else. It is intended for professional use by a knowledgeable professional. If published by the client, it must be published in full, including this disclaimer and limitation of liability.

This report is not an endorsement, recommendation, approval, certification, or criticism by TCNA of any particular product or its application. TCNA recommends that anyone considering the use or installation of a particular product consult with the manufacturer or an industry professional for advice specific to the person's needs and consider any applicable laws, statutes, codes, or regulations relevant to the particular product. TCNA does not know all the different manners and applications in which a client's particular product might be used, and, therefore, it disclaims any and all duty to provide warnings or to further investigate the suitability of the use of a particular product in a particular situation.

Unless otherwise expressly stated, TCNA tested the specific test subject material provided by the client and identified in the lab report, as indicated by the client. TCNA does not independently verify the information provided by the client, and it makes no representation that similar results would be achieved with other, untested materials, even if such other materials purportedly have the same product name, are purportedly of the same or similar type of tile or product made by the client, or are purportedly from the same batch of tile or product. Nor does TCNA state that the date in this report is representative of production occurring at the same time or at any other time. Only the manufacturer may make that claim, based on sampling and quality control parameters beyond the knowledge and control of TCNA. TCNA does not provide any supervision, review, management, or quality control of any manufacturer's production.



100 Clemson Research Blvd., Anderson, SC 29625
Phone 864.646.8453 Fax 864.646.2821
Email testing@tcnatile.com Web www.TCNAtile.com

**PAGE: 7 OF 7** 

# TCNA TEST REPORT NUMBER: TCNA-0756-19

TCNA makes no representation that the client's products are uniform or identical to the test subject material, that the test subject material is suitable for any particular use, application, or installation, or that it will exhibit the same properties when installed or used in a particular manner. The data provided in this report results from standardized laboratory testing performed under laboratory conditions. As such it does not represent all conditions under which the products may be used or subjected. For testing on actual materials being used or considered for a job site, contact TCNA for sampling provisions and possible testing.

This report is intended solely to provide the results of the test procedure stated above as performed on the test subject material provided by the client, and may not be relied on for any other purpose. TCNA MAKES NO OTHER REPRESENTATIONS OR WARRANTIES OF ANY KIND, WHETHER EXPRESS OR IMPLIED. ALL IMPLIED WARRANTIES, INCLUDING, WITHOUT LIMITATION, IMPLIED WARRANTIES OF MERCHANTABILITY, OR FITNESS FOR A PARTICULAR PURPOSE, ARE HEREBY EXPRESSLY DISCLAIMED. IN THE EVENT OF A DISPUTE CONCERNING THIS REPORT, THE EXCLUSIVE REMEDY FOR CLIENT SHALL BE FOR TCNA TO REPEAT THE TEST REQUESTED, BUT IN NO EVENT SHALL TCNA BE LIABLE FOR AN AMOUNT GREATER THAN THE AMOUNT IT RECEIVED FROM CLIENT FOR THE TEST. UNDER NO CIRCUMSTANCES WILL TCNA BE LIABLE TO CLIENT FOR ANY OTHER DAMAGES (NOR SHALL IT BE LIABLE TO ANY OTHER PERSON OR BUSINESS ENTITY FOR ANY DAMAGES), INCLUDING WITHOUT LIMITATION ANY AND ALL DIRECT, INDIRECT, SPECIAL, INCIDENTAL, CONSEQUENTIAL, OR EXEMPLARY DAMAGES, RESULTING, IN WHOLE OR IN PART, FROM ANY USE OF, REFERENCE TO, OR RELIANCE UPON THE REPORT, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGES. TCNA DISCLAIMS ALL LIABILITY TO ANY THIRD PARTY CONCERNING THIS REPORT. THE FOREGOING LIMITATION OF LIABILITY IS A FUNDAMENTAL ELEMENT OF TCNA'S AGREEMENT TO CONDUCT AND PROVIDE THE REPORT.

8/26/19

Katelyn Simpson Laboratory Manager